HDMI 1.4 Switch 5x1



Table of Contents

1.0 Introduction

2.0 Features

3.0 Package

4.9 Specifications

5.9 Front and Back Panel

6,0 Connetion diagram

Thank you for purchasing this product. For optimum performance and safety, please read these instructions carefully before connecting, operating or adjusting this product. Please keep this manual for future reference.

1.0 Introduction

This is a high performance 5 HDMI input and 1 HDMI output switch. It supports HDCP repeater functions and fast switching between any of the HDMI input ports. The system supports all 3D TV formats in addition to all HDTV formats up to 4Kx2K. Furthermore, the remote control gives uses complete control over the selection of sources and makes the device incredibly user friendly.

2.0 Features

- 1. Compliant with HDMI 1.4a, CTS 1.4a, DVI 1.0 standards.
- 2. HDMI 1.4 support: 3D TV support.
- 3. Support 3D Video & 4Kx2K, 8, 10, 12 & 16 bits per color depth.
- 4. Audio support:

Dolby TrueHD, DTS-HD Master Audio 7.1CH

5.Low power consumption, does not require an external power supply

3.0 Package

1. HDMI 1.4 5 by1 Switcher1pcs
2. USB to DC Power Supply cable1pcs
3. Remote controller1pcs
4. IR Receive Extend cable1pcs
5. Operation Manual1pcs

4.0 Specifications

Frequency Bandwidth	2.97Gbps
Input Ports	5 HDMI Female ports, IR Receive port
Output port	1 HDMI Female port
HDMI Audio Output	PCM2, 5.1, 7.1CH, Dolby 5.1, DTS5.1, D-TrueHD, DTS-HD
Dimensions (mm)	87(D) x59.5 (W) x 19(H)
Weight (g)	60
Power Consumption	0.2W
Operating Temperature	0°C ~ 40°C/32°F ~ 104°F
ESD Protection	Human Body Model: ± 8kV (air-gap discharge) ± 4kV (contact discharge)
Storage Temperature	-20°C ~ 60°C / -4°F ~ 140°F

5.0 Front and Back Panel

6.0 Connection diagram









